



- high weight burden
- smooth and quiet running
- suitable for middle or big items

## Specifications


Φ38 single roller expandable conveyor

Model	Unit	Length mm	Width mm	Height mm	Load/Unit kg (no shock load)
FWA-38	1	610-1450	500	700-1000	80
FWA-38	2	980-2480			
FWA-38	3	1350-3510	600	550-700	
FWA-38	4	1720-4540			
FWA-38	5	2090-5570			
FWA-38	6	2460-6600			

## Φ50 single roller expandable conveyor

Model	Unit	Length mm	Width mm	Height mm	Load/Unit kg (no shock load)
FWAH-50	1	700-1600	500	700-1000	100
FWAH-50	2	1120-2700			
FWAH-50	3	1540-3800	600	550-700	
FWAH-50	4	1960-4900			
FWAH-50	5	2380-6000			
FWAH-50	6	2800-7100			

## Roller



Tube Dia.(D)	t	Shaft Dia.(d)	Tube Material	
			Zinc plated steel	Stainless steel
Φ38	1.2	Φ12	√	○
Φ50	1.5	Φ12	√	○

- Design of polymer bearing housing and end cap
- Beautiful, quiet operation

## Order Example

<b>FWA</b>	<b>S</b>	<b>38</b>	<b>G2</b>	<b>60</b>	<b>5</b>	<b>70</b>
Model	Roller Material	OD of Roller	Optional Configuration	Width	Unit No.	Height
FWA	Empty: Zinc Plated Steel	38: Φ38	Empty: None	50: 500	1: 1 unit	70: 700~1000
FWAH	S: Stainless Steel	50: Φ50	G2: Guide Wheel Type	60: 600	2: 2 units	55: 550~700
			H: Straight Handle Type		.....	